

## Appendix A

---

Loudspeaker dimensions.	ii.
Loudspeaker measurement chart-L\H.	iii.
Loudspeaker measurement chart-R\H.	iv.
Loudspeaker impedance curve chart-L\H.	v.
Loudspeaker impedance curve chart-R\H.	vi.
Woofer impedance calculation chart.	vii.
Woofer impedance equalizer calculation chart.	viii.
Woofer Relative efficiency calculation.	viii.
Midrange impedance calculation chart.	ix.
Midrange notch filter calculation chart.	ix.
Tweeter impedance calculation chart.	x.
Tweeter notch filter calculation chart.	x.
Crossover network calculation chart.	xi.
Multiplier table	xii.
Crossover parts list.	xiii.
Inductance chart	xiv.
Crossover schematic diagram.	xv.
Crossover layout diagram.	xvi.

## Loudspeaker Dimensions

Woofer		
Outside diameter	$W_{\text{diam}}$	.....mm.
Woofer radius	$R_w$	.....mm.
Magnet radius	$r_w$	.....mm.
Woofer height	$H_w$	.....mm.
Cone depth	$W_{\text{cone}}$	.....mm.
Flange thickness	$W_{\text{flange}}$	.....mm.
Flange width	$W_{\text{rebate}}$	.....mm.
Cut-out diameter	$W_{\text{hole}}$	.....mm.
Mounting screws		M.....
Midrange		
Outside diameter	$M_{\text{diam}}$	.....mm.
Tube radius	$R_m$	.....mm.
Tube height	$H_m$	.....mm.
Cone depth	$M_{\text{cone}}$	.....mm.
Flange thickness	$M_{\text{flange}}$	.....mm.
Flange width	$M_{\text{rebate}}$	.....mm.
Cut-out diameter	$M_{\text{hole}}$	.....mm.
Mounting screws		M.....
Tweeter		
Outside diameter	$T_{\text{diam}}$	.....mm.
Magnet radius	$R_t$	.....mm.
Cone depth	$T_{\text{cone}}$	.....mm.
Flange thickness	$T_{\text{flange}}$	.....mm.
Flange width	$T_{\text{rebate}}$	.....mm.
Cut-out diameter	$T_{\text{hole}}$	.....mm.
Mounting screws		M.....

## Appendix A

FREQUENCY Hz.	V <sub>S</sub> mvolts.	V <sub>R</sub> volts.	IMPEDANCE Ohms.
10			
15			
20			
25			
30			
35			
40			
50			
60			
70			
80			
90			
100			
200			
300			
400			
500			
600			
700			
800			
900			
1000			
Resonant Frequency - F <sub>s</sub>			


Woofer Impedance Data Chart. (Left hand)

## Appendix A


---

FREQUENCY Hz.	V <sub>S</sub> mvolts.	V <sub>R</sub> volts.	IMPEDANCE Ohms.
10			
15			
20			
25			
30			
35			
40			
50			
60			
70			
80			
90			
100			
200			
300			
400			
500			
600			
700			
800			
900			
1000			
Resonant Frequency - F <sub>s</sub>			

Woofer Impedance Data Chart. (Right hand)



Woofer Impedance Curve Chart. (Left hand)



Woofer Impedance Curve Chart. (Right hand)

## Appendix A

TYPE : .....	P/N : .....	DATE : .....
	LEFT HAND	RIGHT HAND
<b>Woofer parameters :</b> <div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> <math>R_e</math>  <math>F_s</math>  <math>Z_{fs}</math>  <math>Z_{f3}</math>  <math>F_1</math>  <math>F_2</math>  <math>Q_{ts}</math> </div> <div style="width: 30%;"> ..... Ohms.  ..... Hz.  ..... Ohms.  ..... Ohms.  ..... Hz.  ..... Hz.  ..... </div> <div style="width: 30%;"> ..... Ohms.  ..... HZ.  ..... Ohms.  ..... Ohms.  ..... Hz.  ..... Hz.  ..... </div> </div> $Z_{fs} = \frac{V_{s\_}}{V_r} \frac{mV}{V}$ ..... = ..... <b>Crossover points:</b> $F_h = \dots\dots\dots Hz.$ $F_h =$ $F_1 = \dots\dots\dots Hz.$ $X =$ w-woofer $F_l =$ m-midrange t-tweeter  $Z_{f3} = Z_{fs} \times 0.707$	$Z_{fs} = \dots\dots\dots Ohms.$  $Z_{\_\_} = \dots\dots\dots =$  $Z_{\_\_} = \dots\dots\dots Ohms.$  $Z_{\_\_} = \dots\dots\dots =$  $Z_{\_\_} = \dots\dots\dots Ohms.$  $Z_{f3} = .707 \times \dots\dots = \dots\dots \Omega$	$Z_{fs} = \dots\dots\dots Ohms.$  $Z_{\_\_} = \dots\dots\dots =$  $Z_{\_\_} = \dots\dots\dots Ohms.$  $Z_{\_\_} = \dots\dots\dots =$  $Z_{\_\_} = \dots\dots\dots Ohms.$  $Z_{f3} = .707 \times \dots\dots = \dots\dots \Omega$
<b>Speaker Q:</b> $ro = \frac{Z_{fs}}{R_e}$ $Q_{ts} = \frac{F_s}{F_1 - F_2} \times \frac{R_e}{Z_{fs}} \times \sqrt{ro}$	$ro = \dots\dots\dots = \dots\dots\dots$  $Q_{ts} = \dots\dots\dots \times \dots\dots\dots \times \sqrt{\dots\dots\dots}$  $Q_{ts} = \dots\dots\dots$	$ro = \dots\dots\dots = \dots\dots\dots$  $Q_{ts} = \dots\dots\dots \times \dots\dots\dots \times \sqrt{\dots\dots\dots}$  $Q_{ts} = \dots\dots\dots$
Check $F_s$ : ( $\pm 1$ % ) $F_s = \sqrt{F_1 * F_2} \text{ Hz}$	$\sqrt{\dots\dots\dots \times \dots\dots\dots} = \dots\dots\dots Hz$	$\sqrt{\dots\dots\dots \times \dots\dots\dots} = \dots\dots\dots Hz$
<b>Max Output.</b> SPL = 10LOG(P) + S P= rms watts. s=sensitivity.dB@1m/1w	=10LOG.....+..... =..... dB SPL.	=10LOG.....+..... =.....dB SPL.
Calculate $F_5$ : $L_{ref} = R_e \times \sqrt{2}$ Find $L_{ref}$ above $F_s$ and record $F_5$ .(300-1000 Hz.)	= ..... $\times \sqrt{2}.$ = ..... $\Omega$  $F_5 = \dots\dots\dots \text{ Hz.}$	= ..... $\times \sqrt{2}.$ = ..... $\Omega$  $F_5 = \dots\dots\dots \text{ Hz.}$

## Appendix A

$$C7 = \dots\dots\dots \mu F.$$

$$R4 = \dots\dots\dots \Omega.$$

$$F_5 = \dots\dots\dots \text{Hz. (see data chart)}$$

$$\text{Where } L_e = \frac{R_e}{2 \times \pi \times F_5} \times 10^3 = \dots\dots\dots \times 10^3 = \dots\dots\dots \text{mH.}$$

$$C7 = \frac{L_e}{R_e^2} \times 10^3 = \frac{\dots\dots\dots}{(\dots\dots\dots)^2} \times 10^3 = \dots\dots\dots \mu F.$$

$$R4 \text{ (Use a standard 5watt value close to } R_e. \dots\dots\dots \Omega. \\ \text{Check the impedance curve as a reference} \\ \text{and aim to get a straight line)}$$

Note: Use R4 as  $Z_w$  in the woofer crossover calculation chart if using an impedance equalizer.

### Woofer Impedance Equalizer Calculation Chart.

$$\eta_{\text{eff}} = \frac{0.0953 \times (F_s^3 \times V_{as}) \times 10^{-6}}{Q_{es}} = \frac{0.0953 \times ((\dots\dots\dots)^3 \times \dots\dots\dots) \times 10^{-6}}{\dots\dots\dots} = \dots\dots\dots\%$$

$$Q_{es} = \frac{Q_{ms}}{(r_o - 1)} = \frac{\dots\dots\dots}{(\dots\dots\dots - 1)} = \dots\dots\dots$$

$$r_o = \frac{Z_{fs}}{R_e} = \dots\dots\dots = \dots\dots\dots \quad (\text{see data chart for } R_e, Z_{fs}, F_h, F_1)$$

$$Q_{ms} = \frac{F_s \times \sqrt{r_o}}{(F_1 - F_2)} = \frac{\dots\dots\dots \times \sqrt{\dots\dots\dots}}{\dots\dots\dots} = \dots\dots\dots$$

$$V_{as} = 1.15 \times \left( \left( \frac{F_{box}}{F_s} \right)^2 - 1 \right) \times V_{box} = 1.15 \times (\dots\dots\dots - 1) \times \dots\dots\dots \\ = \dots\dots\dots \text{liters}$$

### Woofer Relative Efficiency calculation chart.



## Appendix A

<b>TYPE :</b> ..... <b>P/N :</b> ..... <b>DATE :</b> .....		
	<b>LEFT HAND</b>	<b>RIGHT HAND</b>
<b>Midrange parameters :</b>  <div style="border: 1px solid black; border-radius: 15px; padding: 5px; width: fit-content; margin: 10px auto;"> <b>Crossover point:</b>   <math>L_o</math> .....Hz          &amp;  <math>H_i</math> .....Hz       </div> $Z_{fs} = \frac{V_{s_r}}{V_r} \frac{mV}{V}$  <b>Impedance Z:</b>	$R_e$ ..... Ohms. $F_s$ ..... Hz. $Z_{fs}$ ..... Ohms. $Z_{ml}$ ..... Ohms. $Z_{mh}$ ..... Ohms.  _____ =  $Z_{fs} =$ ..... Ohms.  = _____ =  $Z_{ml} =$ ..... Ohms.  $M_{Lo}$ = _____ =  $Z_{ml} =$ ..... Ohms.  $M_{Hi}$ = _____ =  $Z_{mh} =$ ..... Ohms.	$R_e$ ..... Ohms. $F_s$ ..... Hz. $Z_{fs}$ ..... Ohms. $Z_{ml}$ ..... Ohms. $Z_{mh}$ ..... Ohms.  _____ =  $Z_{fs} =$ ..... Ohms.  = _____ =  $Z_{ml} =$ ..... Ohms.  $Z_{ml} =$ ..... Ohms.

Midrange Impedance Calculation Chart.

**Parameters:**  $F_n =$  .....Hz

$R_3 =$  ..... $\Omega$

$L_6 =$  .....mH

$C_6 =$  ..... $\mu F$

  
 $C_{ideal} = \frac{1}{2 \times \pi \times R_e \times F_n} \times 10^6 = \frac{10^6}{\quad} = \text{.....}\mu F$ 
  
 $L_6 = \frac{1}{C_n \times (2 \times \pi \times F_n)^2} \times 10^3 = \frac{10^3}{\quad} = \text{.....mH}$ 
  
 $R_3 = R_e = \text{.....ohms.}$ 
  

$F_n$  is the frequency of the notch you want to control and is usually equal to  $F_s$ .  
 Calculate  $C_{ideal}$ , then choose the nearest standard value capacitor for  $C_n$  to enable a small enough coil to be wound (<6mH).

Midrange Notch Filter Calculation Chart.

## Appendix A

<b>TYPE :</b> ..... <b>P/N :</b> ..... <b>DATE :</b> .....		
	<b>LEFT HAND</b>	<b>RIGHT HAND</b>
<b><u>Tweeter parameters :</u></b>  <div style="border: 1px solid black; border-radius: 10px; padding: 5px; width: fit-content; margin: 10px auto;"> <b><u>Crossover point:</u></b>            .....Hz         </div> $Z_{fs} = \frac{V_s}{V_r} \frac{mV}{V}$ <b><u>Impedance Z:</u></b>	$R_e$ ..... Ohms. $F_s$ ..... Hz. $Z_{fs}$ ..... Ohms. $Z_t$ ..... Ohms.  _____ =  $Z_{fs} =$ ..... Ohms.  $H_i =$ _____ =  $Z_t =$ ..... Ohms.	$.....$ Ohms. $.....$ Hz. $.....$ Ohms. $.....$ Ohms.  _____ =  $Z_{fs} =$ ..... Ohms.  _____ =  $Z_t =$ ..... Ohms.

**Tweeter Impedance Calculation Chart.**

**Parameters:**      $F_n =$  .....Hz

R2 = .....Ω

L5 = .....mH

C5 = .....μF

$$C_{ideal} = \frac{1}{2 \times \pi \times R_e \times F_n} \times 10^6 = \frac{10^6}{.....} = .....uF$$
  

$$L_5 = \frac{1}{C_n \times (2 \times \pi \times F_n)^2} \times 10^3 = \frac{10^3}{.....} = .....mH$$
  

$$R_2 = R_e = .....ohms.$$
  

$F_n$  is the frequency of the notch you want to control and is usually equal to  $F_s$ .  
 Calculate  $C_{ideal}$ , then choose the nearest standard value capacitor for  $C_n$  to enable a small enough coil to be wound (<6mH).

**Tweeter Notch Filter Calculation Chart.**

Crossover points : .....&.....

Date : .....

$Z_w^* = \dots\dots\dots$      $Z_{mh} = \dots\dots\dots$      $Z_{ml} = \dots\dots\dots$      $Z_t = \dots\dots\dots$

\*Alignment: ..... **n** = C x ..... & L x.....

Woofer :

$$L4 = \frac{Z_w}{2\pi \times F_L \times 10^{-3}} * \mathbf{n} = \dots\dots\dots = \dots\dots\dots \text{mH}$$

$$C4 = \frac{1}{2\pi \times Z_w \times F_L \times 10^{-6}} * \mathbf{n} = \dots\dots\dots 1 \dots\dots\dots = \dots\dots\dots \text{uF}$$

Midrange :

$$L2 = \frac{Z_{mh} \times \sqrt{2}}{4 \times \pi \times (F_h - F_L) \times 10^{-3}} * \mathbf{n} = \dots\dots\dots = \dots\dots\dots \text{mH}$$

$$L3 = \frac{Z_{ml} \times (F_h - F_L)}{2 \times \sqrt{2} \times \pi \times F_m \times 10^{-3}} * \mathbf{n} = \dots\dots\dots \times \dots\dots\dots = \dots\dots\dots$$

$$(\text{Where } F_m = F_h \times F_L \dots\dots\dots = \dots\dots\dots \times \dots\dots\dots = \dots\dots\dots \text{mH})$$

=.....x.....

=.....)

$$C2 = \frac{F_h - F_L}{\sqrt{2} \times \pi \times Z_{mL} \times f_m \times 10^{-6}} * \mathbf{n} = \dots\dots\dots = \dots\dots\dots$$

$$= \dots\dots\dots = \dots\dots\dots \text{uF}$$

$$C3 = \frac{1}{\sqrt{2} \times \pi \times Z_{mh} \times (f_h - F_L) \times 10^{-6}} * \mathbf{n} = \dots\dots\dots 1 \dots\dots\dots = \dots\dots\dots$$

$$= \dots\dots\dots 1 \dots\dots\dots = \dots\dots\dots \text{uF}$$

Tweeter :

$$L1 = \frac{Z_t}{2\pi \times F_h \times 10^{-3}} * \mathbf{n} = \dots\dots\dots = \dots\dots\dots \text{mH}$$

$$C1 = \frac{1}{2 \times \pi \times Z_t \times F_h \times 10^{-6}} * \mathbf{n} = \dots\dots\dots 1 \dots\dots\dots = \dots\dots\dots \text{uF}$$

\* Notes: 1. Use R1 from impedance equalizer chart as  $Z_w$  if using an impedance equalizer on woofer.

2. '**n**' is the multiplier for the different alignments – see Table 1 page 16.

## Crossover Network Calculation Chart.

Filter	1 <sup>st</sup> order	2 <sup>nd</sup> order		
	As calculated with the text book formulas. For higher orders multiply the standard values with the appropriate multiplier.	Butterworth	L/R	Bessel
C1		0.707	0.50	0.57
C4		0.707	0.50	0.57
L1		1.414	2.00	1.74
L4		1.414	2.00	1.74
		n <sup>th</sup> multipliers		

**Table 1**

## Crossover Parts List.

+ = series connection.      \* = parallel connection.

Tweeter: crossover point = .....Hz.

C1 = ..... $\mu$ F = .....@.....v .....@.....v

C5 = ..... $\mu$ F = .....@.....v .....@.....v

C6 = ..... $\mu$ F = .....@.....v .....@.....v

R1 = ..... $\Omega$  = ..... or

R2 = ..... $\Omega$  = .....

L1 = .....mH

L5 = .....mH

Midrange: crossover point = .....&.....Hz.

C2 = ..... $\mu$ F = .....@.....v .....@.....v

C3 = ..... $\mu$ F = .....@.....v .....@.....v

C6 = ..... $\mu$ F = .....@.....v .....@.....v

R3 = ..... $\Omega$  = .....

L2 = .....mH

L3 = .....mH

L6 = .....mH

Woofers: crossover point = .....Hz.

C4 = ..... $\mu$ F = .....@.....v .....@.....v

C7 = ..... $\mu$ F = .....@.....v .....@.....v


L4 = .....mH

R4 = ..... $\Omega$  = .....

Note: Use higher voltage rated caps on parallel connection.

## Crossover Parts List.

# Inductance Chart.



1mm enamelled copper wire.  
38mm wide bobbin.(see fig 21)

